

Mini-SignLED LED

Mini-SignLED is a complete system which is ideal for face and halo illumination in small letters and light boxes.

It's compact size and flexible design fits into all manner of applications where a small stroke width is required.

Sign-LED is conformally coated to resist harsh exterior conditions.

Features:

- A compact low profile flexible system.
- Ideal for face and halo illuminated projects.
- Weather resistant fully sealed LEDs.
- Simple "peel & stick" installation.
- A safe, energy efficient, low voltage solution.
- Available in a variety of colours.

Power Supply:

The Sign-LED's require a constant voltage of 12V DC for optimum operation. The modules can also be dimmed.

Warranty:

The LED warranty is 2 years. The warranty is only applicable if the product is used with approved power supplies.

Mounting:

By means of a self adhesive tape to the rear.

Typical Rating:

Estimated Life :	White:	40,000 Hours
	Red:	50,000 Hours
	Blue:	50,000 Hours

Power Consumption :	White:	0.24W
	Red:	0.21W
	Blue:	0.24W

Viewing Angle: 120°

Input:	12V DC nominal +/- 10%
Operating limits :	-25°C to +50°C, 90% relative humidity
Dimensions:	10 x 18 x 4 mm (not including wires)
Board:	Totally Potted PCB assembly
Wires:	20 swg insulated
Spacing:	8 modules per foot
Polarity:	White wire +DC (positive), grey wire -DC (negative)
Coating:	9001 A/B
UL file, listing:	IP67

