



Product description:

Flexible LED Strip System from Applelec is available on reels in a variety of Kelvin colour temperature matched to our award winning Applelec LED Light Sheet panels, or used independently.

Key features:

Operating voltage: 24V DC

• Beam angle: 120 degree

· Driver type: constant voltage

Operating temperature (range) -20.C to 60.C

Ra>80 (Ra>90 available)

• IP rating: IP20

· Variable cut points

Suitable for:

Header | Refrigeration | Canopy Lighting | Office | Wall Washers | Hotels | Retail

Product information & code selector:

Product code	Voltage	LEDs /m	Wattage	Colour	LED efficiency*	Cut point	Lumen /m
8mm Ribbon	24V DC	128pcs	4W/m	3000K	190lm/W	62.5mm	760 lm/m
8mm Ribbon	24V DC	128pcs	4W/m	4000K	190lm/W	62.5mm	760 lm/m
8mm Ribbon	24V DC	128pcs	4W/m	5000K	190lm/W	62.5mm	760 lm/m
8mm Ribbon	24V DC	128pcs	4W/m	6500K	190lm/W	62.5mm	760 lm/m

(*) according to COMMISSION DELEGATED REGULATION (EU) 2019/2015 of 11th March 2019

PCB Layout:





















